

# Classic/Classic Plus Series

DESIGNED FOR INDUSTRIAL, PLANT  
AND WAREHOUSE APPLICATIONS



## MovinCool® Portable Air Conditioners

TECHNICAL SPECIFICATIONS		Classic 10	Classic Plus 14	Classic Plus 26	Classic 40	Classic 60
Cooling Capacity Rating	Conditions 95°F at 60% RH	10,000 BTU/Hr	13,200 BTU/Hr	24,000 BTU/Hr	39,000 BTU/Hr	60,000 BTU/Hr
Electronic Features	Control Panel	Digital	Programmable	Programmable	Digital	Digital
Electrical Characteristics	Voltage Requirement	1 Phase 115V	1 Phase 115V	1 Phase 208/230 V	3 Phase 220 V	3 Phase 460 V
	Total Power Consumption	1.1 kW	1.3 kW	3.1 kW	4.2 kW	5.9 kW
	Current Consumption	10 Amps	11.9 Amps	14 Amps	14 Amps	8.8 Amps
	Recommended Fuse Size	15	15	20	25	20
	NEMA Plug Configuration	5-15	5-15	6-20	L 15-30	N/A
	Min-Max Voltage	105-125	105-125	198-250	198-250	440-480
Fans	Motor Output High/Low	0.15 kW	0.24/0.19 kW	0.55/0.38 kW	0.75 kW/Evap 0.40 kW/Cond	0.75 kW/Evap 0.40 kW/Cond
Evaporator	Fan Type	Centrifugal	Centrifugal	Centrifugal	Centrifugal	Centrifugal
	Max Air Flow - High/Low	265 CFM	440/380 CFM	708/600 CFM	1060 CFM	1580 CFM
	Max External Static Pressure	0.33 IWG	0.31 IWG	0.54 IWG	1.72 IWG	1.35 IWG
Condenser	Fan Type	Centrifugal	Centrifugal	Centrifugal	Propeller	Propeller
	Max Air Flow - High/Low	740 CFM	880/760 CFM	1680/1460 CFM	2650 CFM	3800 CFM
	Max External Static Pressure	0.13 IWG	0.19 IWG	0.25 IWG	0.05 IWG	0.05 IWG
Compressor	Type	Hermetic Rotary	Hermetic Rotary	Hermetic Scroll	Hermetic Scroll	Hermetic Scroll
	Output	0.7 kW	0.9 kW	1.5 kW	2.3 kW	3.89 kW
Refrigerant		R-410A	R-410A	R-410A	R-410A	R-410A
Dimensions	W x D x H	19 x 26 x 41 in	19 x 26 x 41 in	19 x 29 x 47 in	26 x 43 x 38 in	32 x 49 x 42 in
Net Weight/ Shipping Weight		156/194 lbs	166/197 lbs	235/265 lbs	344/396 lbs	474/566 lbs
Power Cord	Gauge	14 AWG (3 Core)	14 AWG (3 Core)	12 AWG (3 Core)	12 AWG (4 Core)	N/A
	Length	10 ft	10 ft	6 ft	6 ft	N/A
Condensate Tank Capacity		5 gal	5 gal	5 gal	2 @ 5 gal optional	N/A
Operating Conditions	Min-Max (@ 50% RH)	70° - 105° F	70° - 113° F	70° - 113° F	75° - 115° F	75° - 115° F
Max. Duct Length	Per Cold Duct Hose	40 ft	30 ft	60 ft	varies	varies
	Hot Duct Hose (Exhaust)	60 ft	60 ft	45 ft	40 ft	40 ft
Max. Sound Level	With Condensor Duct High/Low	53 dB	57/55 dB	66/64 dB	N/A	N/A
	Without Condensor Duct High/Low	58 dB	60/58 dB	69/67 dB	72 dB(A)	72 dB(A)

**PORTABLE AIR** has the perfect solution for temporary or permanent portable cooling needs.  
Ask us about other MovinCool products.  
Call for pricing on our rental, sales, and lease-to-own programs.

© 2017 PAG RV 11-16 MovinCool® is a registered trademark of DENSO Corporation.



Convenient Offices Nationwide  
Phone: 1-866-948-5300  
Fax: 1-866-948-5400  
E-mail: Sales@portableairgroup.com  
Website: www.portableairgroup.com



## MovinCool® Commercial Price List Classic / Classic Plus Series Portable Air Conditioners

MODEL	PRODUCT DESCRIPTION	MSRP
Classic 10	1-ton 10,000 BTU 115V / 10Amp 1 pH Portable Room Air Conditioner	\$2,830.00
Classic Plus 14	1.1-ton 13,200 BTU 115V / 11.9Amp 1 pH Portable Room Air Conditioner	\$3,395.00
Classic Plus 26	2-ton 24,000 BTU 230V / 10.8Amp 1 pH Indoor & Outdoor Portable Air Conditioner	\$4,540.00
Classic 40	3.3-ton 39,000 BTU 220V / 14Amp 3 pH Industrial Air Conditioning Unit	\$7,890.00
Classic 60	5-ton 60,000 BTU 460V / 8.8Amps 3 pH Industrial Air Conditioning Unit	\$11,045.00

**PORTABLE AIR** has the perfect solution for temporary or permanent portable cooling needs.  
Ask us about other MovinCool products.  
Call for pricing on our rental, sales, and lease-to-own programs.

Rental and Sales of Portable Cooling, Heating, Dehumidification, Filtration and Generating Equipment

Phone: 1-866-948-5300 Fax: 1-866-948-5400

[www.portableairgroup.com](http://www.portableairgroup.com)

Capture this QR code on  
your smart phone to learn  
what **OTHER** products  
we rent/sell/lease.

