

MODEL: 20ACH1811 1.5 TON DELUXE PORTABLE HEAT PUMP

TECHNICAL SPECIFICATIONS

COOLING CAPACITY 16,800 BTUH HEATING CAPACITY 15,000 BTUH

VOLTAGE 115V, 60Hz, 1PH

AMPS 14.1 TOTAL WATTS 1670

IN RUSH AMPS 75

PLUG TYPE 5-20P, LCDI

EER 10.0

COMPRESSOR ROTARY
COMPRESSOR HP 1-1/2
COMPRESSOR LRA 63
EVAP CFM - HIGH 600
EVAP MOTOR HP 1/8

COND CFM 930 COND MOTOR HP 1/8

CONDENSATE TANK 5 GALLON

(Pump Optional)

REFRIGERANT CHARGE 40 oz R-410A

 HEIGHT
 45-3/4 in

 WIDTH
 24 in

 DEPTH
 30 in

 NET WEIGHT
 260 lb

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

- OA Cooling Capacity is total BTUH at 80°DB/67°WB return air 95°F Outdoor at high fan speed
- OA Heating Capacity is total BTUH at 70°DB/60°WB indoor, 47°DB/43°WB Outdoor
- OA Dedicated Circuit and Time Delay fuses/circuit breakers are recommended
- OA EER is determined at high fan speed, with condenser discharge air ducted into separate area
- OA CFM with free discharge
- OA Amps & Watts at 115 Volts

COOLING AMBIENT OPERATING RANGE 65° TO 105°
HEATING AMBIENT OPERATING RANGE 40° TO 85°
NOT APPROVED FOR OUTDOOR USE













MODEL: 20ACH1811 1.5 TON DELUXE PORTABLE HEAT PUMP

PRODUCT FEATURES

- OA SOLID STATE ELECTRONIC CONTROLLER
- OA AUTOMATIC MODE CHANGEOVER
- OA MANUAL OR AUTO 6-SPEED FAN CONTROL
- OA LARGE LED DISPLAY
- A SWIVEL BALL BEARING CASTERS WITH LOCKING FRONTS
- OA CONDENSATE OVERFLOW ALERT
- OA HIGH PRESSURE SAFETY SWITCH
- MASHABLE ELECTROSTATIC AIR FILTERS





