



# PORTABLE COOLING AND SOLUTIONS FOR HEALTHCARE FACILITIES





**Quick, easy installation in hospitals, imaging centers, etc.:** Portable MovinCool units are self-contained. You just roll them in, connect the exhaust duct to a drop ceiling, plug them in and turn them on.



**Cost-effective and flexible:** For areas the main HVAC system does not reach, or when the main system is switched to heating mode.

# **MovinCool® Portable Spot Air Conditioners**

MovinCool portable spot air conditioners provide emergency backup, supplemental or permanent cooling for people and equipment in healthcare facilities.

- **Emergency Preparedness:** When your main HVAC system goes out, rely on MovinCool to provide continuous cooling relief to patients and staff or protect heat-sensitive equipment from malfunctioning or shutting down.
- **Supplemental:** When an emergency room gets hot or overcrowded, or an MRI room or other imaging center needs additional cooling to keep running smoothly, wheel in MovinCool to quickly bring things under control.
- **Permanent:** For areas your main HVAC system does not reach or is inadequate, or to provide cooling to heat-sensitive equipment during cold-weather months when the main HVAC is switched to heating mode, MovinCool is a flexible, cost-effective solution.

MovinCool is a brand of DENSO Corporation, the world's largest manufacturer of spot air conditioners. MovinCool spot air conditioners are backed by a full three-year on-site parts and labor warranty — the strongest in the industry.



# HEALTHCARE COOLING AND HEATING PRODUCTS



### **Multi-Application Cooling**



## Classic 10

10.000 Btu/h 115V, 10A

1-Speed White/Blue Portable A/C Operating Range @50% RH: 70-105 °F



#### Classic Plus 14

13,200 Btu/h 115V, 11.9A

2-Speed White/Blue Portable A/C Operating Range @50% RH: 70-113 °F



#### Classic Plus 26

24,000 Btu/h 208/230V, 15.6/14A 2-Speed White/Blue Portable A/C Operating Range @50% RH: 70-113 °F

### **Heating and Cooling**



#### Climate Pro® 12

Cooling: 10,200 Btu/h; Heating: 9,900 Btu/h

Cooling: 11.1 Amp; Heating: 11.3 Amp 2-Speed White/Gray Portable A/C Operating Range @50% RH: Cooling: 65-95 °F; Heating: 40-80 °F\*



#### Climate Pro® 18

Cooling: 14,600 Btu/h; Heating: 13,700 Btu/h

Cooling: 14.1 Amp; Heating: 14.7 Amp 2-Speed White/Gray Portable A/C Operating Range @50% RH: Cooling: 65-95 °F; Heating: 40-80 °F\*

\*Heating: Without plenum, air entering indoor and outdoor heat exchangers: 40-80 °1 With plenum, air entering indoor heat exchanger: 40-80 °I With plenum, air entering outdoor heat exchanger: 24—80 °F



## **Room and Equipment Cooling**



#### Office Pro® 12

12,000 Btu/h 115V, 11.9A 2-Speed White/Gray Portable A/C Operating Range @50% RH: 65-95 °F



#### Office Pro® 18

16,800 Btu/h 115V. 15.6A

2-Speed White/Gray Portable A/C Operating Range @50% RH: 65-95 °F



#### Office Pro® 24

24,000 Btu/h 208/230V, 13.2A

2-Speed White/Gray Portable A/C Operating Range @50% RH: 65-95 °F



#### Office Pro® 36

36,000 Btu/h 208/230V, 19.6A

2-Speed White/Gray Portable A/C Operating Range @50% RH: 65-95 °F



#### Office Pro® 60

60,000 Btu/h 208/230V. 29A

2-Speed White/Gray Portable A/C Operating Range @50% RH: 65-105 °F



#### Office Pro® 63

60,000 Btu/h

2-Speed White/Gray Portable A/C Operating Range @50% RH: 65-105 °F



All specifications subject to change without notice. Standard warranty includes 12 months on entire unit and compressor. MovinCool offers an industry-best free Extended Warranty Program which includes 3 years for portable models and 2 years for ceiling-mount models for both parts and labor on units. All models feature compressor overload relay and fan motor protection. All models also feature compressor short-cycle protection, return air thermostat and automatic restart, and accommodate a condensate pump kit All models are 50-Hz compatible with a slight performance decrease from specifications listed above.

