

# HEPA Filtration and Negative Air

SPECIFICATIONS	KBA600	KBA1000	KBA1800
<b>DESCRIPTION</b>			
HEPA Filtered	Negative Air Machine	Negative Air Machine	Negative Air Machine
<b>AIR PURIFICATION</b>			
HEPA Filter	99.97% @ > .3 Microns	99.97% @ > .3 Microns	99.97% @ > .3 Microns
<b>FAN DATA</b>			
Fan Type (Centrifugal)	Direct Drive	Direct Drive	Direct Drive
Air Flow (CFM)	600/450 - 2 Speed	1000/850 - 2 Speed	1800/1675/1550 - 3 Speed
<b>ELECTRICAL DATA</b>			
Power Supply	115 V / Single Phase	115 V / Single Phase	115 V / Single Phase
Current Consumption	4.3 Amps	6.2 Amps	9.94 Amps
Power Consumption	0.5 kW	0.6 kW	.83 kW
Maximum Circuit Breaker	20 Amps	20 Amps	20 Amps
Recommended Breaker Size	15	15	15
Minimum Circuit Ampacity	7.7 Amps	8.17 Amps	12.67 Amps
Min/Max Voltage	105 - 125	105 - 125	105 - 125
Power Cord Gauge / Length in Feet	14 AWG / 6'	14 AWG / 6'	14 AWG / 6'
Plug Configuration	NEMA 5 - 15	NEMA 5 - 15	NEMA 5 - 15
<b>DIMENSIONAL DATA</b>			
Width x Length x Height	16.5" x 22.25" x 38"	16.5" x 22.25" x 38"	23" x 26.25" x 46"
Weight	80 Lbs	85 Lbs	135 Lbs
Shipping Weight	115 Lbs	120 Lbs	170 Lbs
<b>SAFETY DEVICE DATA</b>			
Fan Motor Overload	Automatic Internal	Automatic Internal	Automatic Internal
Automatic Restart	Yes	Yes	Yes
<b>OPTIONAL</b>			
Top Discharge Stainless Flange	8" Standard / Optional 12"	10" Standard / Optional 12"	10" Standard / Optional 12"
Optional CK-12S-SS Ceiling Kit	Optional 12" Dia. Ceiling Kit	Optional 12" Dia. Ceiling Kit	Optional 12" Dia. Ceiling Kit
Ceiling Kit - CK - 12SS	12 Lbs	12 Lbs	12 Lbs



**Portable Air Group**

Office: 1.919.240.5930  
 Toll-free: 1.866.948.5300  
 Fax: 1.866.948.5400  
 Web: [portableairgroup.com](http://portableairgroup.com)

Portable Air Conditioners and Heat Pumps – Evaporative Coolers – Air Cooled Chillers – Water Cooled Chillers – DX – Air Handlers  
 Spot Coolers – Generators – Dehumidifiers – Heaters – HEPA Air Cleaners – Advanced BiPolar Ionization – Air Purifiers