DESCRIPTION

Stainless Steel

1800 CFM Portable Air Purifier with HEPA Filtration, UV-C lighting and Advanced Bipolar Ionization.

Optional Negative Air Capability

	Sptional Negative All Capability
AIR PURIFICATION	
HEPA Filter	99.97% @ > 0.3 Microns
UVC Light Wave Length	UVC 30 Watts / Max 85 Watts x3
Ionization	Advanced bipolar ionization (Certified ozone-free)
Prefilter	Yes
UV-C Lights	(3) UV-C 30 watts/Max 85 Watts
UV-C Light Notification	Yes
Filter Change Notification	Yes
FAN DATA	
Fan Type (Centrifugal)	Direct Drive
Air Flow (CFM) at zero external static	1800/1675/1550 – 3-Speed/Quad directional
Air Flow (CFM) with one opening closed	d 1600/1375/1250 - 3 Speed / Quad Directional
ELECTRICAL DATA	
Power Supply (Volts)	115 V / Single Phase
Current Consumption (Amps)	BLE A/10.15
Power Consumption (kW)	0.84
Maximum Circuit Breaker (Amps)	20
Recommended Breaker Size	15
Minimum Circuit Ampacity (Amps)	12.87
Min/Max Voltage	105 - 125
Power Cord	14 AWG / 6 ft.
Plug Configuration	NEMA 5 - 15
DIMENSIONS AND WEIGHT	
Width x Length x Height	23"x 26.25"x 46"
Weight	135 lbs
Shipping Weight	170 lbs
OPTIONAL	
Carbon Filter	Yes
Ceiling Kit - CK - 12SS	12 lbs For Use as a Negative Air Machine
 Top discharge stainless du 	ct collar 12 In.
Flexible Duct	12 in. x 8 ft.
Ceiling tile insert	24 in. x 24 in.
Total Shipping Weight w/ Ceiling Kit	182 lbs
SAFETY DEVICE	
Fan Motor Overload	Automatic Internal
Automatic Restart	Yes
UV-C light "lockout" whenever machine	is opened Yes
CERTIFICATIONS	
ETL (UL 867)	Yes
INTERTEK (UL 2998) Ozone-free	Yes
DISPLAY	
Touchscreen/LED	Yes
CABINET	



Portable Air Filtration and Purification Negative-Air Capable








Office: 1.919.240.5930 Toll-free: 1.866.948.5300 Fax: 1.866.948.5400 Web: portableairgroup.com

Yes





KBX1800

LEGEND

- 1. Room Air Return
- 2. Control Panel (Touch Pad)
- 3. Supplemental Purified Air Supply (Removable cover)
- 4. Cord Storage
- 5. Filter Access Door
- 6. Purified Air Supply

