



OMNIAIRE 1600PAC

HEPA Air Filtration Machine

ORDERING INFO

OmniAire 1600PAC
 Pleated Filter MERV 11
 HEPA Filter 99.99%, 0.3µ (metal frame)
 Intake Manifold Kit (Manifold, Clamp & 3' Duct)
 ABS Plastic Intake Manifold, 12" Dia.
 Flexible Duct, 10" Dia. x 25' L
 Quick Clamp 8-12" Dia.
 Flexible Duct, Wire & Fiber Reinforced
 UVC Replacement 12" Lamp

PART NUMBER

OAI600PAC
 OPF2416
 OAH2418G
 OAIM2000-12KIT
 OAIM2000-12
 OAD12
 QCW14
 OAD12R
 EUV12



UL 507:1997/R:2017-01
 CAN/CSA-C22.2 No. 113-15

The OmniAire 1600PAC machine is equipped with a medical grade 99.99% HEPA filter and UV-C germicidal lights, which work together to eliminate sub-micron particulates and microbial contamination in healthcare facilities, labs and other critical environments. The 1600PAC features variable air flow, quiet operation, upright housing for a small footprint, and medical grade casters for easy mobility. Additional accessories include PEROx air purification module with hydro-peroxide generators, activated carbon filter, intake/outtake manifold, flex ducting and quick clamps.

	OmniAire 1600PAC
Airflow*	200-1600 CFM
Power Requirements	115VAC/60 Hz/10.6 Amp
UVGI Lights	(4) UV-C 15 watt lamps
Controls	ON/OFF, Variable speed controller; 0-3" W.C. pressure gauge; red power indicator light; UVGI Lights ON/OFF switch; hour meter
Filtration	HEPA filter 99.99% 0.3µ; MERV 11 primary/secondary filter
Housing	aircraft grade aluminum with powder coating; silicone sealed before riveting; (1) rubber grip handle; (4) 3" hospital grade locking casters
Size/Weight	26"W x 40"H x 20"L; 135 lbs.

*Airflows based on blower manufacturer curves. Different filters may cause the flow to vary.