FROST FIGHTER INDIRECT FIRE

The perfect solution where clean, dry heat is required to complete a project on time and within budget.



TECHNICAL SPECIFICATIONS

Specification	IDF350 Oil/Diesel	IDF350 LP/NG	IDF500 Oil/Diesel	IDF500 LP/NG	IDF500 HS Oil/Diesel	IDF500 HS LP/NG
Heating Capacity	350,000 BTU/h	350,000 BTU/h	420,000 BTU/h	420,000 BTU/h	420,000 BTU/h	420,000 BTU/h
Electrical Requirements	115V / 15amp	115V / 15amp	115V / 15amp	115V / 15amp	115V / 25amp	115V / 25amp
Air Flow	2,500 CFM	2,500 CFM	3,100 CFM	3,100 CFM	3,250 CFM	3,250 CFM
Static	-	-	0.5"	0.5"	2.3"	2.3"
Motor	0.5Hp	0.5Hp	1Нр	1Нр	1.5Hp	1.5Hp
Shipping Dimensions	83"L x 37"W x 52"H	83"L x 37"W x 52"H	83"L x 37"W x 52"H	83"L x 37"W x 52"H	83"L x 37"W x 52"H	83"L x 37"W x 52"H
Shipping Weight	580lbs	580lbs	580lbs	580lbs	580lbs	580lbs
Approvals / Certification	CSA	ETL	CSA	ETL	CSA	ETL



Office: 1.919.240.5930 Toll-free: 1.866.948.5300 Fax: 1.866.948.5400

Web: portableairgroup.com